Wyse® Z class™

Built for when performance matters most.

WYSE

THE GLOBAL LEADER IN
CLOUD CLIENT COMPUTING

Wyse Z class: **All you need to know. Here.**

Introducing the Wyse Z class

Built for when performance matters most

New Wyse Z class

New Wyse Z class brings unrivalled high performance to users demanding more from their virtual desktops. Five models are available, with Windows Embedded Standard 2009 & 7 operating systems including a cloud PC for WSM.

Thin clients

Z90SW

High performance Windows Embedded Standard 2009 thin client for the most demanding Virtual Desktop Environments.

Z90DW

Highest-performing dual-core thin client based on Windows Embedded Standard 2009.

Z90S7

High performance thin client. Harnesses the rich user experience of Microsoft Windows Embedded Standard 7.

Z90D7

Highest-performing dual-core thin client based on Windows Embedded Standard 7.

Cloud PC

Z00D

Highest-performing dual-core cloud PC for Wyse WSM.

Features Wyse Z class

New Wyse Z class is the ideal high performance cloud client that's perfectly suited to users who're increasingly demanding more from their virtual desktop environments - as well as the traditional cloud client benefits of security and management.

Featuring fast processing, accelerated graphics and multimedia, fast and flexible user connectivity and excellent energy-efficiency never seen before in a cloud client, new Wyse Z class delivers uncompromising high performance when users need it most.

Wyse Device Manager supports Wyse Z class with scalable enterprise-wide management including simple deployment, patching and updates and asset management – all with secure end-to-end encrypted communications.

Like all Wyse cloud clients, new Wyse Z class is one cool operator. Its energy efficient processor – which out-performs other more power hungry alternatives – and silent fan-less design, all contribute to lowering an organization's carbon footprint through power usage and emissions that are a fraction of traditional PC desktops.

Cloud clients

Performance

Connectivity

Mounting options

Green

EarthSmart Computing™

Microsoft Windows Embedded Standard 2009

Windows Embedded Standard 2009

Microsoft Windows Embedded Standard 7

Windows Embedded Standard 7

Software

Thin Client Management

Wyse WDM™

Cloud PC Provisioning

Wyse WSM™

User Experience Optimization

User Experience Acceleration

Take a tour of the Wyse Z class range

High Performance cloud client

Built for when performance matters most

Fast processing.
Accelerated graphics and multimedia.
Fast and flexible user connectivity.
Excellent energy-efficiency.

From the instant the new Wyse Z class boots up it delivers everything that today and tomorrow's users need in order to tackle the most demanding of virtual desktop environments.

At its heart beats the very latest single or dual core AMD G-Series Accelerated Processing Units or APUs, where all the processing, graphics and HD video tasks are performed on the same piece of silicon. Giving a dramatic leap in user experience and the ideal platform to reap the benefits of Wyse cloud, virtualization and management software.

AMD **Fusion**
FAMILY OF APUs
EMBEDDED TECHNOLOGY

Processor

The AMD Embedded G-Series platform is the world's first low power processor and advanced GPU that's integrated into a single embedded Accelerated Processing Unit (APU).

High definition multimedia experience

Display, manipulate and work with stunning high definition multimedia graphics, voice and video in virtual desktop environments that are ready for Unified Communications. That's the promise the Wyse Z class more than delivers on, with great performance across 2D, 3D and HD video applications. Its new design takes them all in its stride and is the first to include hardware accelerated DirectX® 11 graphics with OpenGL 4.0 and OpenCL™ support.

abg WiFi n CERTIFIED

SUPERSPEED USB

Continue tour

Connectivity Fast and flexible

Standard configuration

Front of device

Output:
Digital audio

Input:
8 bit stereo
microphone

2 USB 2.0 ports



DVI-I port

Dual Band 802.11
a/b/g/n Wireless

DisplayPort

2 USB 2.0 ports

10/100/1000 Base-T Gigabit
ethernet port

Kensington lock slot

2 USB 3.0
ports

Option 1

Fiber NIC port

Option 2

2 Serial ports

PS/2 keyboard port

Parallel port for
printer connection

Some features require local OS support
and may not be available with all OSs.

Continue tour

Mounting options

The Wyse Z class family can be placed vertically or horizontally on desktops, mounted to walls and even behind monitors.

Horizontal

Optional feet enable Wyse Z class to be used horizontally.

Back of monitor or wall mounting

An optional VESA mount bracket enables mounting to the rear of a monitor (this requires the four industry standard mounting points to be free). The same bracket can be used for wall mounting.

Vertical

Each Wyse Z class is supplied as standard with feet for vertical use.

Continue tour

Start | Models | Features | Technical | Contact | Print

Green computing without compromise

*Average power usage with device connected to 1 keyboard, 1 PS/2 mouse, and 1 monitor.

EarthSmart Computing™

That's Wyse EarthSmart™ computing

Wyse Z class models are compliant with ENERGY STAR Version 5.0 Thin Client specification, a recognized sign of energy efficiency. Through our EarthSmart Computing initiative we are committed to helping organizations implement a greener computing strategy - one that delivers a more efficient and productive computing experience for your users with a positive effect on energy wastage, heat and carbon emissions.

Green Power

Wyse Z class cloud clients use between 12 and 15 watts of power in typical use*. In comparison, a typical PC would use between 70 and 150 watts. Even in sleep mode Wyse Z class units draw just 2 watts while being fully remotely managed. Then, when you include additional power requirements in the data center, a cloud computing deployment will deliver power savings of between 50 and 90%.

Wyse has implemented an ISO 14001-based environmental management system and WEEE recycling processes, and all Wyse products meet stringent ROHS requirements.

Learn more

Download carbon calculators, fact sheets and white papers from here: **www.wyse.com/green**

Continue tour

Start | Models | Features | Technical | Contact | Print

Operating Systems Microsoft Windows Embedded Standard 2009

Running Windows Embedded Standard (WES) on Wyse thin clients gives IT departments the ability to deploy fully functional desktop clients with better manageability and significantly lower total cost of ownership than personal computers.

Wyse WES 2009-based thin clients can run 32 bit Microsoft Windows applications, either locally or from servers, with the inbuilt flexibility to add and support a host of desktop peripherals with permission from the IT administrator.

Full support is provided for RDP 7.0, Citrix ICA 11.2, VMware View 4.0.1 and Internet Explorer 8.

Secure write-protected thin client desktops.

This robust and flexible operating system is further enhanced by the Wyse file-based Write Filter that enables you to protect the files, folder and/or entire volumes from accidental changes or user customization. On rebooting, the thin client simply returns to its original state thus preventing any possible damaging modification either from users or malware.

Wyse customized image support

Wyse technicians are prepared to help you customize Windows Embedded Standard 2009 to your exact requirements in order to create custom-built images for subsequent enterprise-wide deployment, management and update through Wyse Device Manager.

Contact your Wyse Partner for further details.

Windows Embedded Standard 2009

Continue tour

Start | Models | Features | Technical | Contact | Print

Operating Systems Microsoft Windows Embedded Standard 7

New Windows Embedded Standard 7 (WES 7) delivers a wealth of enhanced deployment, user experience and management benefits to Wyse desktops, mobiles and thin clients deployed across an organization's virtualized network.

Richer user experience.

Wherever they are - deskbound or mobile - with Microsoft Windows Embedded Standard 7 your users can benefit from the rich user experience of the Aero interface and the power, familiarity and reliability of the Windows 7 operating system in a highly customizable and componentized form.

Full support is provided for Remote Desktop Protocol (RDP) 7.0 to provide seamless connectivity to Windows Server 2008 R2 and virtual desktop infrastructure scenarios. The Wyse-enhanced WES7 platforms include additional features supporting the latest Citrix Online Plug-in and VMware View 4.5 to fit the needs of your most sophisticated users and making it an optimum OS for organizations wanting broad support for Cloud computing and desktop virtualization. Citrix Online Plug-in provides the HDX user experience and View 4.5 provides localization and Virtual Printing.

The platform also features additional Windows technology innovations to drive rich, immersive user experiences, including Internet Explorer 8.

There's full support and inbuilt flexibility too, to add and support a host of desktop peripherals with permission from the IT administrator.

Easier to manage and deploy.

Now, with WES7, deploying 32-bit capable thin clients is easier and more manageable than ever before and reflects the direct working relationship between Wyse and Microsoft.

The support for Domain Join and group policies through Active Directory, along with support for management infrastructures like Microsoft System Center Configuration Manager (SCCM), help with management and integration of thin clients into existing desktop management infrastructures.

Wyse Device Manager (WDM) addresses key management requirements for deploying powerful thin clients. With its centralized management and administration, WDM helps IT departments deliver more effective remote thin client support while minimizing end user downtime. While to help IT and Customer Service staff, a simple USB imaging solutions, Wyse USB Firmware Tool, allows to quickly and easily manage image supported devices.

Enterprise-wide consistency

Wyse Embedded Standard 7 and Wyse provide the ideal, cost effective opportunity to deploy a consistent, high performance operating system across Wyse cloud clients.

Continue tour

Thin Client Management Wyse Device Manager

Wyse Device Manager (WDM) addresses key management requirements for deploying powerful thin clients. With its centralized management and administration WDM helps IT departments deliver more effective remote thin client support while minimizing end user downtime.

Security is assured with HTTPS based imaging, updates and downloads.

WDM delivers organization-wide benefits:

Operations	Centralized management. Collect and organize asset information.
Administration	Health status reports. Automated client settings. Update client firmware and add applications.
End User IT Costs	Easier more effective remote support. Create custom scripts and packages.
Minimize downtime	Restart or reset thin clients in less than a minute. Enforce policies. Minimize user errors.

At a glance features.

Security	HTTPS Based Imaging / Updates. Fully Encrypted Network Traffic. Delegated Admin Access (MS AD) Support.
No-Hassle Deployment	Complete Device Imaging / Patching / Updates Bandwidth Throttling for Efficiency / Reliability Software Updates and Add-ons
Device Administration and Monitoring	Device Health Status / Reporting Remote Shadowing / Control Default Device Configuration
Scalability	Distributed Architecture Microsoft SQL Database Support Multiple Remote Repository Support
Complete Asset Visibility	Automated device discovery Detailed Hardware Asset information Installed Software Asset information.

Wyse WDM™

Continue tour

Cloud PC Provisioning Wyse WSM

Enterprise computing from the cloud is here. Whatever you want. Wherever you need it.

That's the thinking behind Wyse WSM. It's a dynamic on-demand streamed computing environment where everyone gets their preferred operating systems, applications, user data and documents: Wherever they are and whenever they need them.

And Wyse WSM goes beyond the traditional VDI model too - with full support for mobile workers and remote branch offices. Wyse WSM effectively changes the rules on what's possible and opens up the benefits of high performance desktops to enterprise users: Wherever they are.

Better than a PC could ever be.

With Wyse WSM users - such as those in the financial or retail industries - are given a fresh computer with their chosen PC operating system, applications and files all preloaded and ready-to-go, every time they sit down and start-up their powerful desktop devices known as Wyse 'cloud PCs'.

Wyse cloud PCs feature powerful processors that enable them to run full PC operating systems and applications locally, while keeping their documents and data secure on central Wyse WSM servers. Enabling existing PC users to continue to use all their familiar operating systems and applications seamlessly - but with greater reliability and better overall performance than a full PC - with the result that many users don't even realize they're using a cloud PC.

Wyse WSM™

And - better still, Wyse WSM features a highly secure, robust and resilient network design that's ideal for remote offices and mission critical deployments such as the defence industry.

With everything managed, updated, configured remotely and securely, Wyse WSM is everything a PC promises. Minus the headaches.

Continue tour

Start | Models | Features | Technical | Contact | Print

wyse.com

User Experience Optimization Wyse TCX™ Suite

with Collaborative Processing Architecture™

Wyse TCX delivers an amazing user experience in one software suite.

Wyse TCX Suite of virtualization software enriches the user experience by removing the limitations previously associated with thin clients. It enhances, not replaces, key protocols like ICA/HDX and RDP by adding key features to make each more valuable.

Multi-display

Ensures application windows and dialog boxes are multi-monitor aware when using more than one monitor.

USB Virtualization

Enables plug and play peripheral support for virtual desktop environments.

- Redirect and use local USB devices in virtual desktops.
- Deploy virtual desktops to knowledge workers with special device access needs.
- Enable a broad set of USB peripherals including webcams and headsets.

Multimedia acceleration

Streamlines the delivery of video and audio content to the local client for a rich user experience within a thin client computing architecture.

- Accelerates Mpeg1, Mpeg2, WMV, Mpeg4 Part 2, AC3, AAC, MP3, WAV, WMA media types.
- Collaborative Processing Architecture enhances server scalability, and network utilization by off-loading multimedia rendering to the client.

Flash acceleration

Flash acceleration helps thin client users to experience improved Flash video performance. While the Flash player continues to run server-side, the resulting images are transcoded and redirected to the client for fast rendering. The technology allows for greater control of frame rate and compression and supports enhanced playback of YouTube-style flash videos in Internet Explorer.

Bi-directional sound

Enables bi-directional audio in virtual desktop environments, enabling solutions such as VOIP, digital dictation or voice recognition to be deployed.

Continue tour

Virtualization Software Wyse Virtual Desktop Accelerator

Removing the barriers of network latency

Wyse Virtual Desktop Accelerator (VDA) enables virtualized desktop and thin computing environments to be deployed to areas where network latency has, to date, presented operational barriers. Now, with Wyse VDA, more users can receive the full benefits of Wyse thin computing – with the best PC experience over virtualized desktops.

Wyse VDA is a software-only solution for Wyse thin clients and supported PCs that delivers the best user experience for the allocated network bandwidth by neutralizing the effects of network latency and packet loss. Making 'thin' suitable for more remote-site, branch, or field-based users.

Wyse VDA works with instead of replacing existing RDP and ICA protocols, accelerating them by up to 20 times on networks faced with latencies up to and beyond 300ms, and at least 768kbps bandwidth.

At a glance features.

- Software-only acceleration of virtual desktops and applications
- Accelerates existing Citrix ICA and Microsoft RDP protocols
- Works on WANs and 'fat, long pipes'
- Accelerates connections to Citrix XenApp, Citrix XenDesktop, VMware View and Microsoft Terminal Server and Microsoft Hyper-V VDI
- Enhances Wyse TCX software suite functionality across wide-area networks
- Enables Wyse Collaborative Processing Architecture across wide-area networks
- Administrator console provides control of maximum bandwidth per connection
- Leverages built-in security of underlying protocols (128-bit encryption for RDP and ICA).

Take tour again

Start | Models | Features | Technical | Contact | Print

Technical Wyse Z class specifications

The Wyse Z class is configured to feature Wyse WSM cloud software and Microsoft Windows Embedded Standard 2009 and Windows Embedded Standard 7 operating systems.

Want to learn more? Simply click the relevant icon.

Cloud clients

Wyse Z class specifications

Microsoft Windows Embedded Standard 2009

Windows Embedded Standard 2009

Microsoft Windows Embedded Standard 7

Windows Embedded Standard 7

Cloud software

Cloud PC Provisioning

Wyse WSM™

Specifications

Wyse Z90SW, Z90DW, Z90S7 & Z90D7 thin clients and Z00D cloud PC.

Processors	AMD G-T52R 1.5 GHz Processor with AMD Radeon™ HD 6310 Graphics Dual core AMD G-T56N 1.6 GHz Processor with AMD Radeon™ HD 6310 Graphics
Memory	Z90SW & Z90DW 2GB Flash / 1GB RAM Z90S7 & Z90D7 4GB Flash / 2GB RAM Z00D 0GB Flash / 2GB RAM Expandable up to 32GB Flash / 4GB RAM
I/O peripheral support	One DisplayPort. (Optional DisplayPort to DVI-I adapter available) One DVI-I port. DVI to VGA (DB-15) adapter included Six total USB ports: Four USB 2.0 ports (two front, two rear) Two SuperSpeed USB 3.0 ports on rear (backwards compatible with USB 2.0) Enhanced USB Keyboard with Windows Keys (104 keys) and PS2 mouse port PS/2 Optical mouse included **Factory options:** Legacy connectivity - adds 2 serial ports, 1 parallel port and 1 PS/2 keyboard port
Networking	10/100/1000 Gigabit Ethernet **Factory options:** Dual Band 802.11 a/b/g/n Wireless Fiber NIC network connectivity
Display	VESA monitor support with Display Data Control (DDC) for automatic setting of resolution and refresh rate DisplayPort: 2560x1600@32bpp DVI-I: 1920x1200@32bpp Dual display: 1920x1200@32bpp
Audio	Output: 1/8-inch mini jack, full 16 bit stereo, 48KHz sample rate, Digital Audio Out, Internal Mono speaker Input: 1/8-inch mini jack, 8 bit stereo microphone

Physical characteristics	Height: 7.87 inches (200mm) Width: 1.85 inches (47mm) Depth: 8.85 inches (225mm)
Shipping Weight	6 lbs. (2.7kg)
Mountings	Vertical feet standard Horizontal feet optional Optional VESA mounting bracket
Device Security	Built-in Kensington security slot (cable sold separately)
Power	Worldwide auto-sensing 100-240 VAC, 50/60 Hz. Energy Star V.5.0 Phase V external and EuP compliant power adapter Average power usage with device connected to 1 keyboard with 1 PS/2 mouse and 1 monitor: Under 15 Watts
Temperature Range	Operating: 32° to 104° F (10° to 40° C), horizontal and vertical positions Storage : 14° to 140° F (-10° to 60° C)
Humidity	20% to 80% condensing 10% to 95% non-condensing
Safety Certifications	German EKI-ITB 2000, ISO 9241-3/-8 cULus 60950, TÜV-GS, EN 60950 FCC Class B, CE, VCCI, C-Tick WEEE, RoHS Compliant Energy Star & EPEAT listed* (pending)
Warranty	Three-year hardware warranty

AMD Fusion FAMILY OF APUs EMBEDDED TECHNOLOGY

a b g WiFi n CERTIFIED

SUPERSPEED USB

* Not applicable to some option/memory configurations.

Software specifications

Microsoft Windows Embedded Standard 2009

Firmware features	Microsoft Windows Embedded Standard 2009 Microsoft Internet Explorer 8.0 resident: HTML, JavaScript, XML, Active X Sun JRE, Media Player, Citrix Web Interface RDP 7.0 resident Citrix Online Plugin 11.2 resident (ICA 11.2) VMware View 4.0.1 client resident Ericom PowerTerm® Terminal Emulation provides 30-plus terminal emulations Windows Media Player 11, .NET 3.5
Server OS Infrastructure Support	Citrix XenApp / Citrix Presentation Server Citrix XenDesktop VMware View Microsoft Windows Terminal Server 2003 & 2008
Application Framework	.Net 3.5
Security	File Based Write Filter (FBWF) Microsoft Baseline Security Analyzer (MBSA)
Set-up and Configuration	Boot from local flash Microsoft Windows WES7 user interface languages: U.S, Optional add-ons
Keyboard language support	U.S. English (standard), French, German, Spanish, U.K. English, 40 other languages included
Protocol Support	TCP/IP, DNS, DHCP, PXE
Management	Remote management, configuration, and upgrades through Wyse Device Manager Complete image upgrade Wake terminal remotely (Wake-on LAN) Terminal configuration (IP information, name, etc.) Remote screen shadowing of entire desktop (Wyse Remote Shadow) Reporting, Asset management SMS Altiris

Wireless support	802.11 b/g/n support with external wireless adapter or internal wireless adapter option WPA-2, WEP, WPA wireless authentication PEAP-GTC wireless authentication protocol with optional Juniper Odyssey Client Supports PC-Card wireless adapters from: Cisco, D-Link, Netgear, US Robotics, Trendware
Plug-ins	Adobe Flash Player Adobe Shockwave Microsoft Silverlight
Wyse TCX Suite	Advanced support for innovative Wyse TCX Suite of virtualization software that both works with and enhances ICA and RDP (instead of replacing them) featuring: - Multimedia acceleration - the power to run rich multimedia files formats ultilizing Wyse Collaborative Processing Architecture (CPA) that intelligently redirects the necessary processing tasks between the thin client and the server. - Multi-display - ensures that windows and dialogue boxes behave the way users expect when using more than one monitor. - USB Virtualization - makes thin client-attached USB devices visible to virtual desktops and applications, with full IT control. - Bi-directional sound - enables virtual desktops and applications to receive and transmit high quality audio without compromise. - Flash acceleration - helps users of thin clients to experience improved Flash performance.

Software specifications

Microsoft Windows Embedded Standard 7

Firmware features	Microsoft Windows Embedded Standard 7 (WES7) Microsoft Internet Explorer 8.0 resident: HTML, JavaScript, XML, Citrix Web Interface RDP 7.0 resident Citrix Online Plugin 11.2 resident (ICA 11.2) Citrix XenDesktop VMware View 4.0.1 client resident (VMware View 4.5 supported) Ericom PowerTerm® Terminal Emulation provides 30-plus terminal emulations Windows Media Player 12
Server OS Infrastructure Support	Citrix XenApp / Citrix Presentation Server Citrix XenDesktop VMware View Microsoft Windows Terminal Server 2003 & 2008 R2
Security	File Based Write Filter (FBWF)
Set-up and Configuration	Boot from local flash Microsoft Windows WES7 user interface languages: U.S, Optional add-ons
Keyboard language support	U.S. English (standard), French, German, Spanish, U.K. English, 40 other languages included
Protocol Support	TCP/IP, DNS, DHCP, PXE
Management	Remote management, configuration, and upgrades through Wyse Device Manager Complete image upgrade Terminal configuration (IP information, name, etc.) Reporting, Asset management SCCM Simple USB imaging solution with Wyse USB Firmware Tool

Wireless support	802.11 b/g/n support with external wireless adapter or internal wireless adapter option WPA-2, WEP, WPA wireless authentication PEAP-GTC wireless authentication protocol with optional Juniper Odyssey Client Supports PC-Card wireless adapters from: Cisco, D-Link, Netgear, US Robotics, Trendware
Plug-ins	Adobe Flash Player Microsoft Silverlight
Wyse TCX Suite	Advanced support for innovative Wyse TCX Suite virtualization software that both works with and enhances ICA and RDP (instead of replacing them) featuring: - Multimedia acceleration - the power to run rich multimedia files formats ultilizing Wyse Collaborative Processing Architecture (CPA) that intelligently redirects the necessary processing tasks between the thin client and the server. - Multi-display - ensures that windows and dialogue boxes behave the way users expect when using more than one monitor. - USB Virtualization - makes thin client-attached USB devices visible to virtual desktops and applications, with full IT control. - Bi-directional sound - enables virtual desktops and applications to receive and transmit high quality audio without compromise. - Flash acceleration - helps users of thin clients to experience improved Flash performance.

Software specifications

Wyse WSM

Device Hardware Requirements	Windows XP Pro - Minimum processor speed 800 MHz (1GHz or higher is recommended) - Mind. 256 MB (1GB or higher is recommended) Vista and Windows 7 - Minimum processor speed 1 GHz (1.5GHz or higher is recommended) - Mind. 1 GB (2GB or higher is recommended) - Flash size/local storage – none needed. If the device has flash it can be used as a local cache for offline mode.
Server Requirements	Minimum processor speed 1GHz (3GHz or higher is recommended). Server Operating System: Windows XP Pro SP3, Windows Server 2003, Windows Server 2008 and 2008 R2
Network Requirements	Server Lan Speed = Minimum 100Mbps (1Gbps and up is recommended) Device Lan Speed = Minimum 10Mbps (100 Mbps full duplex is recommended)
Operating Systems Supported	Microsoft Windows XP Microsoft Windows Vista Microsoft Windows 7
Databases supported	Microsoft SQL 2005 and 2008 (Server and Express Editions)
Built-in high Availability	- Database availability using SQL clustering. - Built-in server high availability through WSM Server Grouping feature. - Server to Server Fail-over Capability.
Fast and Easy Installation	- Installing Wyse WSM is simply a matter of running a single, graphical installer. - The installer checks for all the prerequisite components before installation.

Web-based Admin Console	- Allows IT administrators to access Wyse WSM from any browser. - Control the entire installation from a central location. - Dramatically simplifies administration, saving IT time and user downtime. - Wizards to guide the user through specific tasks.
Operation System and Application Imaging Tools	- Imaging tool simplifies the process of creating an OS image for the specific hardware configuration and an application image for all hardware configurations. - All OS and application images are ready for deployment once created, no further modifications needed.
Application Subscription Management	Use flexible application deployment methods: - Auto-subscribed applications are ready for use when user logs in for the first time. - Manual subscriptions allow users the flexibility to use applications only when needed. - Mandatory subscriptions that cannot be unsubscribed by users.
Protected System Drive	- Allows administrators to protect the system drive from end user initiated updates. - Prevents changes to operating system drive except by administrators, helping stop viruses, spyware, or malware from infecting the device.

Software specifications continued

Wyse WSM continued

Operating System Streaming	- Wyse WSM provides an on-demand operating system to Wyse cloud PCs or diskless PCs on the network. - Innovative technology makes each Wyse cloud PC or diskless PC think there is a virtual hard disk attached to the device. - Only those bits needed for the normal device operation are sent in order to reduce network traffic. - Operating-system images can be shared across multiple devices, making management easier.
Flexible Boot Options	- Each device can boot from four operating system image assignments. - Administrators can assign or let users choose which operating system they want to boot. - First disk mode for the default OS image to boot from every time device starts up. - First available mode to boot from the first responding server in order to balance loads.
Application License Management and Metering	- Wyse WSM provides the infrastructure to collect information about the application license-usage across the enterprise. This information allows IT organizations to save money associated with application licenses. - Licenses can be stored for all the applications deployed. It also enforces license compliance. - Types of licenses that can be controlled include: 1) Time-based licenses (valid for X days). 2) Number of concurrent users.

Modes of Operation	Wyse WSM allows administrators to choose modes of operation for the OS: - Private Mode – for administration of operating system images. - Shared Mode – has two additional modes of normal operation: 1) Volatile – returns desktop to pristine state after a device reboot. 2) Persistent – remembers any user settings after a device reboot.
Remote Servers for Scalability	- IT administrators can deploy multiple remote servers to improve scalability of the overall solution. - Central management of remote servers allows easy deployment of the solution across different geographic locations.
Comprehensive Reporting	- Easy ad-hoc reporting based on flexible parameters. - Reports are delivered through HTML, giving you the flexibility to output in any form. - License-metering reports can be used to make proactive purchasing decisions. - License-audit reports can be used for compliance purposes.
Desktop Compatibility	Wyse WSM works with Wyse C00LE, V00LE, R00L/E, Z90D and X00C/L family cloud PCs as well as with existing thin clients, diskless PCs and virtual-desktop systems.

Contact Wyse

Wyse Technology Inc.

3471 North First Street,
San Jose,
CA 95134-1801

Visit our website at:

http://www.wyse.com
or send an email to: sales@wyse.com

Wyse Sales

800 GET WYSE (800 438 9973)

International customers please dial:

00 1 408 473 1200

Wyse Support Portal

Wyse Support Portal provides a fast and accurate way to communicate interactively with Wyse Customer Support, and helps us respond to your requests more quickly.

http://support.wyse.com/selfservice.html

Wyse offers cloud client computing sales, service and support expertise around the globe. Click for contact details.

©2011 The Wyse logo and Wyse are trademarks of Wyse Technology Inc. Other product names mentioned herein are for identification purposes only and may be trademarks and/or registered trademarks of their respective companies. All specifications are subject to change without notice. Whilst we make every effort to ensure the accuracy of the details, specifications, models, images and benefits featured in this datasheet, we cannot be held responsible for any errors and/or omissions. If you have any queries regarding Wyse products please contact your authorized regional Wyse Partner or representative for further information and assistance. Some features require support by server operating system and protocol. Approved final 180211.

WYSE wyse.com

THE GLOBAL LEADER IN
CLOUD CLIENT COMPUTING

Wyse® Z class™

Built for when performance matters most

WYSE

THE GLOBAL LEADER IN
CLOUD CLIENT COMPUTING

Wyse Z90SW, Z90DW, Z90S7 & Z90D7 Thin Clients and Z00D Cloud PC

High performance

Fast processing. Accelerated graphics and multimedia. Fast and flexible user connectivity. Excellent energy-efficiency.

From the instant the new Wyse Z class - the world's first self configuring windows-based Thin Client boots up - it delivers everything that today and tomorrow's users need in order to tackle the most demanding of virtual desktop environments.

At its heart beats the very latest single or dual core AMD G-Series Accelerated Processing Units or APUs, where all the processing, graphics and HD video tasks are performed on the same piece of silicon. Giving a dramatic leap in user experience and the ideal platform to reap the benefits of Wyse cloud, Virtualization and Management software.

High definition multimedia experience

Display, manipulate and work with stunning high definition multimedia graphics, voice and video in virtual desktop environments that are ready for Unified Communications. That's the promise the Wyse Z class more than delivers on, with great performance across 2D, 3D and HD video applications. Its new design takes them all in its stride and is the first to include hardware accelerated DirectX® 11 graphics with OpenGL 4.0 and OpenCL™ support.

Energy efficient

Throughout its long life span the Wyse Z class has the least possible impact on working environments and energy consumption.

Its low energy processor out-performs other more power hungry alternatives, while minimal heat emissions permit a fan-less design that lowers power requirements. It all adds up to an advanced high performance Thin Client that's compliant with the Energy Star Version 5.0 Thin Client specification.

At a glance

Performance

The AMD Embedded G-Series platform is the world's first low power processor and advanced GPU that's integrated into a single embedded Accelerated Processing Unit (APU).

Connectivity

Two SuperSpeed USB 3.0 ports, four USB 2.0 ports,. Gigabit networking connectivity, optional single (A/B/G) and dual-band (N) WiFi.

Microsoft Windows Embedded Standard 2009 and 7

Take advantage of fast, secure and reliable access to the power of Windows Embedded Standard.

Thin client management

Wyse Device Manager supports Wyse Z class with scalable enterprise-wide management including simple deployment, patching and updates and asset management – all with secure end-to-end encrypted communications.

Wyse WSM provisioning software

Provides compact, energy efficient and productive 'Cloud PCs' with all the dynamic user experience of PCs - without their risks and complexities.

Green

Wyse Z class thin clients use under 15 watts in idle mode – less than the nearest rivals; saving critical carbon output and vital energy budgets. Energy Star Version 5.0 Thin Client specification.

Specifications

Processors	AMD G-T52R 1.5 GHz Processor with AMD Radeon™ HD 6310 Graphics Dual core AMD G-T56N 1.6 GHz Processor with AMD Radeon™ HD 6310 Graphics
Memory	Z90SW & Z90DW 2GB Flash / 1GB RAM Z90S7 & Z90D7 4GB Flash / 2GB RAM Z00D 0GB Flash / 2GB RAM Expandable up to 32GB Flash / 4GB RAM
I/O peripheral support	One DisplayPort. (Optional DisplayPort to DVI-I adapter available) One DVI-I port. DVI to VGA (DB-15) adapter included Six total USB ports: Four USB 2.0 ports (two front, two rear) Two SuperSpeed USB 3.0 ports on rear (backwards compatible with USB 2.0) Enhanced USB Keyboard with Windows Keys (104 keys) and PS2 mouse port PS/2 Optical mouse included **Factory options:** Legacy connectivity - adds 2 serial ports, 1 parallel port and 1 PS/2 keyboard port
Networking	10/100/1000 Gigabit Ethernet **Factory options:** Dual Band 802.11 a/b/g/n Wireless Fiber NIC network connectivity
Display	VESA monitor support with Display Data Control (DDC) for automatic setting of resolution and refresh rate DisplayPort: 2560x1600@32bpp DVI-I: 1920x1200@32bpp Dual display: 1920x1200@32bpp
Audio	Output: 1/8-inch mini jack, full 16 bit stereo, 48KHz sample rate, Digital Audio Out, Internal Mono speaker Input: 1/8-inch mini jack, 8 bit stereo microphone
Physical characteristics	Height: 7.87 inches (200mm) Width: 1.85 inches (47mm) Depth: 8.85 inches (225mm)
Shipping Weight	6 lbs. (2.7kg)
Mountings	Vertical feet standard Horizontal feet optional Optional VESA mounting bracket
Device Security	Built-in Kensington security slot (cable sold separately)
Power	Worldwide auto-sensing 100-240 VAC, 50/60 Hz. Energy Star V.5.0 Phase V external and EuP compliant power adapter Average power usage with device connected to 1 keyboard with 1 PS/2 mouse and 1 monitor: Under 15 Watts
Temperature Range	Operating: 32° to 104° F (10° to 40° C), horizontal and vertical positions Storage : 14° to 140° F (-10° to 60° C)
Humidity	20% to 80% condensing 10% to 95% non-condensing
Safety Certifications	German EKI-ITB 2000, ISO 9241-3/-8 cULus 60950, TÜV-GS, EN 60950 FCC Class B, CE, VCCI, C-Tick WEEE, RoHS Compliant Energy Star & EPEAT listed* (pending)
Warranty	Three-year hardware warranty

* Not applicable to some option/memory configurations.

Wyse Technology Inc.
3471 North First Street
San Jose, CA 95134-1801

Visit our website at:
http://www.wyse.com
Or send email to: sales@wyse.com

Wyse Sales
800 GET WYSE
(800 438 9973)

Wyse Support Portal:
A fast and accurate way to communicate interactively with Wyse Customer Support.
http://support.wyse.com/selfservice.html

©2011 The Wyse logo and Wyse are trademarks of Wyse Technology Inc. Other product names mentioned herein are for identification purposes only and may be trademarks and/or registered trademarks of their respective companies. Specifications subject to change without notice. Some features require support by server operating system and protocol. Approved final 290311.

WYSE
THE GLOBAL LEADER IN CLOUD CLIENT COMPUTING
wyse.com